

### Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

#### Listing of Claims:

1. (Currently Amended) An ink jet printhead comprising:  
a plurality of nozzles; and

at least one respective heater element corresponding to each nozzle,

wherein the printhead is configured to receive ~~a supply of an~~ ejectable liquid at an ambient temperature, and wherein

each heater element is arranged for being in thermal contact with ~~the~~  
~~ejectable a bubble-forming~~ liquid,

each heater element is configured to heat at least part of the ~~bubble~~  
~~ejectable-forming~~ liquid to a temperature above its boiling point to form a gas  
bubble therein thereby to cause the ejection of a drop of the ejectable liquid  
through the corresponding nozzle; and

each heater element is configured such that the energy required to be applied  
thereto to heat said part to cause the ejection of ~~a~~-said drop is less than the  
energy required to heat a volume of said ejectable liquid equal to the volume  
of ~~a~~-said drop, from a temperature equal to said ambient temperature to said  
boiling point.

2. (Currently Amended) The printhead of claim 1 being configured to support the  
~~bubble-ejectable-forming~~ liquid in thermal contact with each said heater element, and ~~to~~  
~~support the ejectable liquid~~ adjacent each nozzle.

3. (Cancelled).

4. (Original) The printhead of claim 1 being configured to print on a page and to be a  
page-width printhead.

5. (Currently Amended) The printhead of claim 1 wherein each heater element is in the  
form of a suspended beam, arranged for being suspended over at least a portion of the  
~~bubble-forming-ejectable~~ liquid so as to be in thermal contact therewith.

6. (Currently Amended) The printhead of claim 1 wherein each heater element is configured such that an actuation energy of less than 500 nanojoules (nJ) is required to be applied to that heater element to heat that heater element sufficiently to form ~~a~~-said bubble in the bubble-forming liquid thereby to cause the ejection of ~~a~~-said drop.

7. (Original) The printhead of claim 1 comprising a substrate on which the nozzles are disposed, the substrate having a substrate surface, wherein each nozzle has a nozzle aperture opening through the substrate surface, and wherein the areal density of the nozzles relative to the substrate surface exceeds 10,000 nozzles per square cm of substrate surface.

8. (Currently Amended) The printhead of claim 1 wherein each heater element has two opposite sides and is configured such that ~~a~~-said gas bubble formed by that heater element is formed at both of said sides of that heater ~~element~~.

9. (Original) The printhead of claim 1 wherein the bubble which each heater element is configured to form is collapsible and has a point of collapse, and wherein each heater element is configured such that the point of collapse of a bubble formed thereby is spaced from that heater element.

10. (Original) The printhead of claim 1 comprising a structure formed by chemical vapor deposition (CVD), said nozzles being incorporated on the structure.

11. (Cancelled).

12. (Original) The printhead of claim 1 comprising a plurality of nozzle chambers, each corresponding to a respective nozzle, and a plurality of said heater elements being disposed within each chamber, the heater elements within each chamber being formed on different respective layers to one another.

13. (Original) The printhead of claim 1 wherein each heater element is formed of solid material more than 90% of which, by atomic proportion, is constituted by at least one periodic element having an atomic number below 50.

14. (Currently Amended) The printhead of claim 1 wherein each heater element includes solid material and is configured for a mass of less than 10 nanograms of the solid material of that heater element to be heated to a temperature above said boiling point thereby to heat said part of the ~~bubble forming~~ejectable liquid to a temperature above said boiling point to cause the ejection of ~~a~~said drop.

15. (Original) The printhead of claim 1 wherein each heater element is substantially covered by a conformal protective coating, the coating of each heater element having been applied substantially to all sides of the heater element simultaneously such that the coating is seamless.

16. (Currently Amended) A printer system incorporating a printhead, the printhead comprising:

a plurality of nozzles; and

at least one respective heater element corresponding to each nozzle,

wherein the printhead is configured to receive ~~a supply of an~~ejectable liquid at an ambient temperature, and wherein

each heater element is arranged for being in thermal contact with ~~a~~the ~~bubble forming~~ejectable liquid,

each heater element is configured to heat at least part of the ~~bubble forming~~ejectable liquid to a temperature above its boiling point to form a gas bubble therein thereby to cause the ejection of a drop of the ejectable liquid through the corresponding nozzle; and

each heater element is configured such that the energy required to be applied thereto to heat said part to cause the ejection of ~~a~~said drop is less than the energy required to heat a volume of said ejectable liquid equal to the volume of ~~a~~said drop, from a temperature equal to said ambient temperature to said boiling point.

17. (Currently Amended) The system of claim 16 being configured to support the ~~bubble forming~~ejectable liquid in thermal contact with each said heater element, and ~~to support the~~ejectable liquid adjacent each nozzle.

18. (Cancelled).

19. (Original) The system of claim 16 being configured to print on a page and to be a page-width printhead.

20. (Currently Amended) The system of claim 16 wherein each heater element is in the form of a suspended beam, arranged for being suspended over at least a portion of the bubble-forming/ejectable liquid so as to be in thermal contact therewith.

21. (Currently Amended) The system of claim 16 wherein each heater element is configured such that an actuation energy of less than 500 nanojoules (nJ) is required to be applied to that heater element to heat that heater element sufficiently to form a said bubble in the bubble-forming/ejectable liquid thereby to cause the ejection of a said drop.

22. (Original) The system of claim 16 comprising a substrate on which the nozzles are disposed, the substrate having a substrate surface, wherein each nozzle has a nozzle aperture opening through the substrate surface, and wherein the areal density of the nozzles relative to the substrate surface exceeds 10,000 nozzles per square cm of substrate surface.

23. (Currently Amended) The system of claim 16 wherein each heater element has two opposite sides and is configured such that a said gas bubble formed by that heater element is formed at both of said sides of that heater element.

24. (Original) The system of claim 16 wherein the bubble which each heater element is configured to form is collapsible and has a point of collapse, and wherein each heater element is configured such that the point of collapse of a bubble formed thereby is spaced from that heater element.

25. (Original) The system of claim 16 comprising a structure formed by chemical vapor deposition (CVD), said nozzles being incorporated on the structure.

26. (Cancelled).

27. (Original) The system of claim 16 comprising a plurality of nozzle chambers, each corresponding to a respective nozzle, and a plurality of said heater elements being disposed

within each chamber, the heater elements within each chamber being formed on different respective layers to one another.

28. (Original) The system of claim 16 wherein each heater element is formed of solid material more than 90% of which, by atomic proportion, is constituted by at least one periodic element having an atomic number below 50.

29. (Original) The system of claim 16 wherein each heater element includes solid material and is configured for a mass of less than 10 nanograms of the solid material of that heater element to be heated to a temperature above said boiling point thereby to heat said part of the bubble forming liquid to a temperature above said boiling point to cause the ejection of a said drop.

30. (Original) The system of claim 16 wherein each heater element is substantially covered by a conformal protective coating, the coating of each heater element having been applied substantially to all sides of the heater element simultaneously such that the coating is seamless.

31. (Currently Amended) A method of ejecting a drop of an ejectable ~~fluid liquid~~ from a printhead, the printhead comprising a plurality of nozzles and at least one respective heater element corresponding to each nozzle, the method comprising the steps of:

receiving a supply of an ejectable liquid, at an ambient temperature, to the printhead;

applying heat energy to at least one heater element corresponding to a said nozzle;

heating that at least one heater element, by the step of applying heat energy, so as to

heat at least part of ~~the bubble-forming-ejectable liquid~~ which is in thermal contact with the ~~at least one heated heater element~~ to a temperature above the boiling point of the ~~bubble-forming-ejectable liquid~~;

generating a gas bubble in the ~~bubble-forming-ejectable liquid~~ by said step of heating;

and

causing a drop of the ejectable liquid to be ejected through the nozzle corresponding to the at least one heater element by said step of generating a gas bubble, wherein said applied heat energy is less than the energy required to heat a volume of said ejectable liquid equal to the volume of said drop, from a temperature equal to said ambient temperature to said boiling point.

32. (Currently Amended) The method of claim 31 comprising, before said step of heating, the steps of:

disposing the ~~bubble-forming~~ejectable liquid in thermal contact with the heater elements; and

~~disposing the ejectable liquid~~ adjacent the nozzles.

33. (Cancelled).

34. (Currently Amended) The method of claim 31 wherein each heater element is in the form of a suspended beam, the method further comprising, prior to the step of applying heat energy, the step of disposing the ~~bubble-forming~~ejectable liquid such that the heater elements are positioned above, and in thermal contact with, at least a portion of the ~~bubble-forming~~ejectable liquid.

35. (Original) The method of claim 31 wherein the step of applying heat energy to at least one heater element comprises applying an actuation energy of less than 500nJ to each such heater element.

36. (Original) The method of claim 31 comprising the step of providing the printhead, wherein the printhead includes a substrate on which said nozzles are disposed, the substrate having a substrate surface and the areal density of the nozzles relative to the substrate surface exceeding 10,000 nozzles per square cm of substrate surface.

37. (Original) The method of claim 31 wherein each heater element has two opposite sides, and wherein, in the step of generating a gas bubble, the bubble is generated at both of said sides of each heated heater element.

38. (Original) The method of claim 31 wherein, in the step of generating a gas bubble, the bubble is collapsible and has a point of collapse, and is generated such that the point of collapse is spaced from the at least one heated heater element.

39. (Original) The method of claim 31 comprising the step of providing the printhead, including forming a structure by chemical vapor deposition (CVD), the structure incorporating the nozzles thereon.
40. (Cancelled).
41. (Original) The method of claim 31 wherein the printhead has a plurality of nozzle chambers, each chamber corresponding to a respective nozzle, the method further comprising the step of providing the printhead including forming a plurality of said heater elements in each chamber, such that the heater elements in each chamber are formed on different respective layers to one another.
42. (Original) The method of claim 31 comprising the step of providing the printhead, wherein each heater element is formed of solid material more than 90% of which, by atomic proportion, is constituted by at least one periodic element having an atomic number below 50.
43. (Original) The method of claim 31 wherein each heater element includes solid material and wherein the step of heating the at least one heater element includes heating a mass of less than 10 nanograms of the solid material of each such heater element to a temperature above said boiling point.
44. (Original) The method of claim 31 comprising the step of providing the printhead, including applying to each heater element, substantially to all sides thereof simultaneously, a conformal protective coating such that the coating is seamless.